

High-Pressure Cleaning Equipment



Hot & Cold Water Pressure Washers Biodegradable Pressure Washer Detergents Genuine Pressure Washer Parts & Accessories



Electric Powered Hot Water Models



- Oil Fired or LP Fired
- 2.1 or 2.2 GPM @ 1300 or 1500 PSI
- 2 or 2.3 HP
- 115 Volt / 1 Phase
- Direct-Drive Pump



- Oil Fired
- 4.0 to 5.0 GPM @ 2300 to 3000 PSI
- 5 to 10 HP
- 208, 230, 460 or 575 Volt / 1 or 3 Phase
- Belt-Drive Pump



- Oil Fired
- 3 GPM @ 1000 PSI
- 2 HP
- 115 Volt / 1 Phase
- Direct-Drive Pump



- LP or Natural Gas Fired
- 4.0 GPM @ 2000 or 2300 PSI
- 5 or 6.2 HP
- 208, 230, 460 or 575 Volt / 1 or 3 Phase
- Belt-Drive Pump



- Oil Fired, LP, or Natural Gas Fired
- 2.8 or 3.5 GPM @ 1500 to 3000 PSI
- 3 to 8.2 HP
- 208 or 230 Volt / 1 Phase
- Direct & Belt-Drive Pumps



- LP or Natural Gas Fired
- 4.0 to 5.0 GPM @ 3000 PSI
- 7.5 to 10 HP
- 208, 230, 460 or 575 Volt / 1 or 3 Phase
- Belt-Drive Pump

Our Featured Wash Bay Hot Water Models - Electric Powered



- Oil Fired, Natural Gas or optional LP-Fired
- 5.9 6.0 GPM @ 2500 or 3000 PSI
- 10 15 HP
- 208, 230, 460 or 575 Volt / 1 or 3 Phase
- Belt-Drive Pump



- Oil Fired, Natural Gas or optional LP-Fired
- 7.8 GPM @ 3000 PSI
- 20 HP
- 208, 230, 460 or 575 Volt / 3 Phase
- Belt-Drive Pump



- Oil Fired, Natural Gas or optional LP-Fired
- 9.5 GPM @ 2500 PSI
- 20 HE
- 208, 230, 460 or 575 Volt / 3 Phase
- Belt-Drive Pump

Gas Powered Hot Water Models



- Oil Fired
- 3.0 to 4.6 GPM @ 3000 to 3500 PSI
- 270 to 479 CC's
- Honda or Vanguard Engine
- Belt-Drive Pump



- Oil Fired
- 2.7 to 3.8 GPM @ 2400 to 3500 PSI
- 211 to 389 CC's
- Honda GX or Subaru Engine
- Direct-Drive Pump



- Oil Fired
- 4.3 to 5.6 GPM @ 3000 to 4000 PSI
- 479 to 688 CC's
- Honda or Vanguard Engine
- Belt-Drive Pump



- WIODEL 30
- 6.0 GPM @ 3000 PSI
- 688 CC's

Oil Fired

- Honda Engine
- Belt-Drive Pump

Diesel / Electric Powered Hot Water Models



- Diesel Fired / Diesel Powered
- 5.0 to 9.5 GPM @ 2500 to 3200 PSI
- 599 to 1123 CC's
- Kubota Engine
- Belt-Drive Pump



- All Electric
- 3.46 or 3.9 GPM @ 2000 or 3000 PSI
- 6.2 or 7.5 HP
- Baldor Motor
- Belt-Drive Pump



- Heating Modules (used to convert cold water models into a hot water unit)
- Natural Gas, Oil Fired or optional LP-Fired
- 6 GPM to 10 GPM
- 115V / 1PH

Mobile Cleaning Systems



All 1200 Series Models as well as Models 965B, 1075BE, 1075SSE and 1080BE from the Gas Engine Series will mount on the Trail Blazer

- Affordable trailer unit for mobile cleaning anywhere
- Load capacity 3500 lbs.
- 200 gallon polyethylene water tank with 7-inch access port
- 15-inch spoke wheels
- 39-inch tongue length with swing-away hinge
- Swivel jack handles up to 1000 lbs.
- 2-inch ball coupler for quick & easy hook-up of the trailer

Pressure Washer Accessories

Hotsy biodegradable detergents are available for specific cleaning applications:

- Transportation specialty detergents
- Degreasers
- All-purpose cleaners
- Specialty cleaners
- Institution & Food Preparation

Hotsy detergents contain advanced-formula

HCC additives to prevent scale build-up and fight corrosion in your equipment.

Hotsy accessories can provide faster, more efficient cleaning. Speak with

your local Hotsy dealer to find out which accessory may be best for your cleaning needs. Popular accessories include:

- Flat Surface Cleaners
- Extension Wands
- Hose Reels
- Specialty Nozzles
- Sandblast Kits
- Foamers






Gas Powered Cold Water Models

(Shown in Large Cage ver sion. Small 2-wheel version

- 3.7 to 4.5 GPM @ 3500 to 5000 PSI
- 389 to 688 CC's
- Honda GX, Vanguard or Kohler Engine
- Belt-Drive Pump
- One diesel powered model



- 2.3 to 3.8 GPM @ 2400 to 3500 PSI
- 163 to 389 CC's
- Honda GX Engine
- Direct-Drive Pump



- 2.8 to 3.7 GPM @ 2000 to 3500 PSI ■ 163 to 389 CC's
- Honda GX Engine
- Belt-Drive Pump
- BXA Series features aluminum frame



- 2.3 to 3.8 GPM @ 2300 to 3500 PSI
- 160 to 389 CC's
- Honda GC or GX Engines
- Direct-Drive Pump
- DBA Series features aluminum frame



- 2.5 GPM @ 2700 PSI
- 169 CC Subaru Engine
- Direct-Drive Pump
- Placed in UTV's with load capacity greater than 1,000 lbs.



- 2.3 GPM @ 2300 to 2400 PSI
- 160 to 163 CC's
- Honda GC or GX Engine
- Direct-Drive Pump

Electric Powered Cold Water Models




- 2.75 to 5.93 GPM @ 1000 to 3000 PSI
- 2 to 10 HP
- Baldor Motor
- 115, 208, 230 or 460 Volt / 1 or 3 Phase Belt-Drive Pump
- Belt-Drive Pump



- 5.0 GPM @ 5000 PSI
- 20 HP @ 1750 RPM
- 230 or 460 Volt / 3 Phase



- 3.0 to 3.5 GPM @ 1000 to 2000 PSI
- 1.5 to 5 HP
- Baldor Motor
- 115 or 230 Volt / 1 Phase
- Direct-Drive Pump



- 4 to 5 GPM @ 2000 to 300 PSI
- 2 HP
- 230, 460 or 575 Volt / 1 or 3 Phase
- Belt-Drive Pump
- Programmable Smart Control



- 1.8 to 3 GPM @ 1000 to 1400 PSI
- 2 HP
- 115 Volt / 1 Phase
- Direct-Drive Pump

Distributed by:

